

Ready-mixed Concrete

1. IDENTIFICATION OF SUBSTANCE / PREPARATION AND COMPANY

Companies: - Tudor Griffiths Limited
Porthmadog Concrete Limited
Powys Ready Mixed Concrete Company Limited
TG Concrete Bridgnorth Limited

Office location: - Wood Lane Quarry, Ellesmere, Shropshire, SY12 OHY

Telephone: - 01691 62 62 62

Products: Ready-mixed Concrete

Intended use: - Various applications in construction and civil engineering projects.

HAZARD INFORMATION

2. COMPOSITION

Concrete

Mixture of natural aggregates, cement and water. Other ingredients may include admixtures, Pulverised Fuel Ash (PFA) and Ground Granulated Blast-furnace Slag (GGBS). Such additions are made to alter / improve the working characteristics of the material or to affect / enhance its properties once hardened.

3. HAZARDS IDENTIFICATION

Wet Concrete

- Contact with eyes may cause irritation or, in severe cases, alkali burns. Skin contact may provide allergic contact dermatitis in those sensitised to chromium compounds which occur in cement.
- Prolonged skin contact may result in irritant contact dermatitis and/or ulceration.
- Prolonged skin contact may cause sensitisation to chromium compounds.

Dry concrete dust

Inhalation of silica particles in dust created by cutting or surface treatment of hardened concrete containing high silica aggregates (e.g. flint, quartzite, granite) may cause respiratory damage.

EMERGENCY ACTION

4. FIRST AID MEASURES

Wet concrete

- Eye contact: Irrigate eye(s) immediately with clean water for at least 10 minutes. Seek immediate medical attention.
- Skin contact: Wash thoroughly with clean water as soon as contamination occurs.

Includes indirect contact through saturated clothing which should be changed.

Dry concrete dust

- Eye contact: Irrigate eye(s) immediately with clean water. Seek medical attention.
- Skin contact: Wash with clean water.
- Inhalation/ingestion: Remove patient to fresh air.

5. FIRE FIGHTING MEASURES

None needed: Materials do not support combustion.

6. ACCIDENTAL RELEASE MEASURES

Personal protection

- Avoid contact with skin and eyes
- Wear impervious protective clothing

(See under section 8 EXPOSURE CONTROLS/PERSONAL PROTECTION)

Environmental measures

Prevent from entering drains, sewers or water courses.

Method of cleaning

Recover bulk spillage, without delay and while material is still in nonhardened (plastic) state, using suction system or mechanical shovel.

PRECAUTIONS

7. HANDLING & STORAGE

Wet concrete

- Avoid direct skin and eye contact with wet concrete
- Do not kneel or sit on wet concrete
- Exercise care adjacent to deep sections of newly-placed concrete which is still fluid/plastic.
- *For personal protection, also see section 8*

Dry concrete dust

- Minimise dust creation wherever possible
- *For personal protection, also see section 8*

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Wet concrete

- Hand protection: impervious gloves
- Eye protection: suitable protection is advisable where there is risk of accidental exposure/splashing.
- Skin protection: long sleeved clothing, full-length trousers, and impervious boots. Also kneepads, if kneeling down to provide a surface finish.

Dry concrete dust

NOTE: Occupational Exposure Standards (OES) or Maximum Exposure Limits (MEL) for inhalable and respirable dusts are set by the Health & Safety Commission.

These are published annually in HSE Guidance Note EH40.

The following limits (8 hour time-weighted averages) are given in EH40/99:

- | | 8 Hour TWA |
|---------------------------------|--------------------------|
| • Total inhalable dust | 6mg/m ³ OES |
| • Respirable dust | 2.4mg/m ³ OES |
| • Respirable crystalline silica | 0.1mg/m ³ MEL |

Engineering control measures: containment and local exhaust ventilation where airborne dust exposure is likely to reach exposure limits.

Respiratory protection: suitable respiratory protective equipment to HSE approved standard if engineering control measures are insufficient

Hand protection: abrasive-resistant gloves

Eye protection: anti-dust goggles to approved HSE standard.

PRODUCT INFORMATION

9. PHYSICAL & CHEMICAL PROPERTIES

Detailed properties vary according to:

- the specific mix, and
- the ingredients added to affect the working characteristics of the material

All mixes are:

- Abrasive
- Alkaline (typically pH10-14)

9. STABILITY & REACTIVITY

Not applicable

10. TOXICOLOGICAL INFORMATION

Wet concrete

- Eye contact: may cause irritation or, in severe cases, alkali burns
- Skin contact: (short-term exposure) may cause alkali burns; may cause acute allergic dermatitis in people sensitised to chromium compounds.

(Chronic long-term exposure) may cause irritant contact dermatitis; may lead to sensitisation of the skin to chromium compounds.

Dry concrete dust

- Eye contact: may cause transient irritation
- Skin contact: (brief/occasional) no harm likely
- Inhalation: inhalation of large quantities of dust or dust containing respirable silica (generated by cutting, drilling etc.) may cause progressive lung damage, leading to permanent disability and, in extreme cases, to premature death.
- Ingestion: no harm likely

11. ECOLOGICAL INFORMATION

No data is available on the preparations themselves. When used as intended, no environmental impact is anticipated.

If spillage occurs, do not allow material to enter drains, sewers or water courses.

WASTE DISPOSAL

12. DISPOSAL CONSIDERATIONS

Not hazardous. However, disposal subject to local authority current requirements/regulations.

ADDITIONAL INFORMATION

13. TRANSPORT INFORMATION

Not hazardous: - no vehicle labelling required.

14. REGULATORY INFORMATION

Chemicals (Hazard Information and Packaging for Supply) Regulations 2009

Danger Classification: IRRITANT (+ hazard symbol)

- R38 Irritating to the skin
- R41 Risk of serious damage to the eyes
- R43 May cause sensitisation by skin contact
- S24 Avoid contact with skin
- S25 Avoid contact with eyes
- S26 In case of contact with eyes, rise immediately with plenty of water and seek medical advice.

OTHER STATUTORY PROVISIONS

Health & Safety at Work etc. Act 1974

Consumer Protection Act 1987

Control of Substances Hazardous to Health Regulations (COSHH) 2002

Construction (Design & Management) Regulations 2015

Environmental Protection Act 1990

IMPORTANT NOTES:

The information contained in this Safety Data Sheet does NOT constitute the user's own assessment of workplace risk as required by other safety legislation. If purchasing on behalf of a third party who will work with the material, it is your statutory duty to pass on this information to them BEFORE such work begins.

9. OTHER INFORMATION

Data and advice in this Safety Data Sheet is provided to alert all purchasers and users to the possible hazards of use when the material is used as intended. This information should enable them to take necessary precautions to protect the health and safety of all personnel.

GUIDANCE REFERENCES

Available from HMSO, HSE area offices, or local authority Environmental Health Departments:

- EH40: Occupational Exposure Limits
- A Step-by-Step Guide to COSHH (HS(G)97)

Further copies of Safety Data Sheet available from;

Tudor Griffiths Limited
Porthmadog Concrete Limited
Powys Ready Mixed Concrete Co Limited
TG Concrete Bridgnorth Limited

Wood Lane, Ellesmere, Shropshire, SY12 OHY
Tel.: (01691) 626262 Fax: (01691) 626263 www.tgggroup.co.uk

The information and advice contained in this leaflet is given by TUDOR GRIFFITHS LIMITED, PORTHMADOG CONCRETE LIMITED, POWYS READY MIXED CONCRETE CO LIMITED AND TG CONCRETE BRIDGNORTH LIMITED in good faith and, to the best of the Company's knowledge, was accurate at time of publication. However, no liability or responsibility of any kind can be accepted by the Company, its staff or representatives for problems arising directly or indirectly from the content of this leaflet, from the actions or omissions of third parties or from poor site practice.